

POCSAG receiver with 7" touch monitor

## Functions

- ✓ Alert message now readable from a greater distance
- ✓ Alert print function via standard printer
- ✓ Incoming alert can trigger audio playback of MP3 files



## Features

- ✓ Receive and display POCSAG alerts
- ✓ 7" (17.8cm) colour touchscreen; Resolution 800x480 pixels
- ✓ Display alert text in 5 x 16/ 6 x 18 or 9 x 28 characters as well as dynamic optimised screen filling up to 240 characters
- ✓ Automatic printout of the alarm text on common inkjet or laser printers via USB interface, as well as manually via print button; multiple printout can be configured
- ✓ Alert time and current time displays
- ✓ Output of alert signals as MP3 files via integrated speaker
- ✓ Line audio output – e.g. for controlling external PA systems
- ✓ switching output via potential free relay; Configurable switching time
- ✓ Alert timer: Alert flashes for configurable time or until acknowledgement
- ✓ Operations such as scrolling text, scrolling messages, save, delete, print etc. via touchscreen soft-buttons
- ✓ reception sensitivity <-104 dBm
- ✓ 32 RIC areas, in total more than 1 million RICs
- ✓ DiCal-IDEA 128 bit encryption (optional)

## Side and rear view



## Printer drivers

- ✓ Currently available printer drivers (01/17):
- ✓ Samsung Xpress M2020, 2022, 2025 and 2026
- ✓ HP Deskjet 2540 All-in-one Series
- ✓ HP Officejet Pro 8620 e-All-in-One Printer series
- ✓ additional printer drivers on request.

## Interfaces

- ✓ USB A socket for printer control
- ✓ USB B socket for programming
- ✓ Line output for audio
- ✓ Switching output via relay (plug-in terminal 3.5mm)
- ✓ Antenna socket (BNC)
- ✓ 12V DC socket for plug-in power supply



## Accessoires

- ✓ Rod antenna ( $\lambda/4$ ) for 2m band, 165-174 MHz
- ✓ Plug-in power supply 230 VAC / 12 VDC,
- ✓ 1000 mA

## Technical specifications

- ✓ Temperature range 0 – 70 degrees Celsius
- ✓ Voltage 12V DC; 230V/ 12V plug-in power supply included
- ✓ Power consumption approx. 500mA
- ✓ Dimensions (WxHxD) approx. 197 x 127 x 126 mm
- ✓ Weight approx. 680g
- ✓ Compliance RoHS, CE,

Swissphone  
Telecommunications GmbH  
Industriestraße 51  
D-79194 Gundelfingen  
www.swissphone.de  
vertrieb@swissphone.de

Zugang zu der DiCal-Toll-Benutzergruppe

